















TECHNICKÝ LIST

			na HDF desce	lepené
	Rozměry, celková tloušťka	EN 427 & EN 428	1235 × 305 × 9,5 mm	1235 × 305 × 1,5 mm
	Třída zátěže	EN 16511	23/ 32 / 41	23/ 32 / 41
	Celková hmotnost	EN 430	9 300 g/m ²	3 600 g/m ²
	Útlum hluku	EN ISO 717-2	14 dB	4 dB
	Vliv kolečkové židle	EN 425	typ W (měkká kolečka)	typ W (měkká kolečka)
	Reakce na oheň	EN ISO 9239-1	B _{fl} s1	B _{fl} s1
	Tepelný odpor	EN 12524	0,088 m ² K/W	0,019 m ² K/W
	Rozměrová stabilita	EN 434	< 0,05 %	< 0,10 %
	Zbytkový otlak	EN 433	max. 0,03 mm	max. 0,03 mm
	Stálobarevnost	ISO 105	6 / 7	6 / 7
	Chemická odolnost	EN 423	dobrá odolnost	dobrá odolnost
	Hodnota emisí		v souladu s AgBB	v souladu s AgBB
	Bobtnavost 24 h	EN 317	< 8 %	0 %
	Pevnost spoje	ISO 24334	HDF > 450 kg/m	-
	Elektrostatické vlastnosti	EN 1815	< 2 kV	< 2 kV
	Protiskluznost	EN 51130	R10	R10



Ecoline Click



Ecoline lepený